

Quantum™ 20

ITE series

Signature features

20 channels

Next generation automatic with SmartFocus

Clients can experience superior automatic performance with the optimal blend of 3 listening environments plus a unique specialized treatment of music. In addition, the integration of SmartFocus™ further improves speech understanding in noise or provides optimal comfort automatically

Pinna Effect

This feature uses sophisticated calculations to recreate natural directionality

Natural Sound Balance

An adaptive feature to minimize artifacts that can occur when amplified sound combines in the ear canal with direct sound. Natural Sound Balance continuously monitors these sounds and makes precision adjustments to preserve a clear, balanced signal

Automatic Adaptation Manager

Allows for an automatic and smooth adjustment period for the client; providing the best possible first fit acceptance combined with maximum long-term benefit for speech understanding

Next generation feedback manager

Harnessing the power of Unitron's new Era™ platform, the next generation feedback manager offers maximum usable gain by suppressing feedback transients before they become audible

Self learning and LearnNow

Capable of learning client preferences for SmartFocus and volume control in all programs. Clients are able to accelerate the learning by using the LearnNow™ feature

Wireless technology

Binaural Phone – streams audio to the non-phone ear, allowing for binaural hearing while using a phone

DuoLink – program, volume and SmartFocus adjustments conducted on one hearing instrument are automatically transferred to the other ear

uDirect™ (optional) – wireless interface between hearing instruments and Bluetooth® enabled devices (eg. cell phones)

uTV™ (optional) – streams audio from a TV or audio source to the uDirect

Remote controls (optional)

Choice of remote controls for essential or fully featured functionality;
• Unitron remote control • Smart Control

Smart Alert System (optional)


A unique solution that provides awareness of household alerts

Additional features


- 3 manual + 3 wireless streaming programs
- IntelliVent technology
- Multiband adaptive directional microphone
- AntiShock™
- MyMusic™
- Speech enhancement LD
- Noise reduction
- Wind noise manager
- Data logging
- Easy-t
- DAI through uDirect
- Optional wireless programming with iCube




Fitting guides




Quantum 20 M
(moderate power)



Quantum 20 P
(power)



Quantum 20 HP
(high power)



Quantum 20 SP
(super power)

Quantum 20 is suitable for fitting mild to severe hearing losses and can fit audiogram configurations ranging from reverse to precipitously sloping.

Quantum 20 ITEs offer flexible ordering!

Wireless and directional microphone guide:

- 13 Always wireless, always directional
- 312 Available any combination
- 10A Always non-wireless and omni microphone







Battery and style guide: S=Standard; O=Optional

Battery	FS	HS	CA	MC	CIC
13	S	O	O		
312	O	S	S	Omni	
10A	O	O	O	S	S

Quantum 20 ITE series

Quantum 20 M (moderate power) Quantum 20 P (power) Quantum 20 HP (high power) Quantum 20 SP (super power)

ANSI 3.22 2003/IEC 118-7 2CC COUPLER TECHNICAL DATA

Reference test frequency - IEC 118-7 (kHz)		1.6	1.6	1.6	1.6
		OSPL90			
Maximum (dB SPL)		112	117	122	130
Nominal (dB SPL)		109	114	119	127
ANSI HFA (dB SPL)		103	109	114	120
at RTF (dB SPL)		103	109	113	127
		Full on gain (input 50 dB SPL)			
Maximum (dB)		40	50	60	70
ANSI HFA (dB)		37	45	54	62
at RTF (dB)		35	43	53	70
		Basic frequency response (ANSI 2003)			
Frequency range (Hz)		100-7500	100-7500	100-7100	100-5500
Reference test gain (dB)		26	32	37	43
Current drain at RTG (mA) 10A/312/13		1.2/1.2/1.2	1.2/1.2/1.2	1.2/1.2/1.2	--/1.2/1.2
Typical battery life (h) 10A/312/13		80/150/260	80/150/260	80/150/260	--/180/260
Equivalent input noise at RTG (dB SPL)		19	19	19	19
Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)		1.5/1.5/1.0	1.5/1.5/1.0	1/1/1	1/1/1
		Induction coil sensitivity (ANSI 2003, 31.6 mA/m)			
HFA SPLITS/STS (dB SPL/dB)		88/2	94/2	99/2	104/1
					






Quantum P: mic at 70 dB SPL vs. induction coil at 100 mA/m

— Mic
— Induction coil

Electromagnetic compatibility

EMC immunity by ANSI C63.19-2001 EMC, omni/telecoil M4/T4 M4/T4 M4/T4 M4/T4

IEC 118-0 OES COUPLER TECHNICAL DATA

Reference test frequency - IEC 118-o (kHz)		1.6	1.6	1.6	1.6
		OSPL90			
Maximum (dB SPL)		120	123	128	133
at RTF (dB SPL)		111	118	121	132
		Full on gain (input 50 dB SPL)			
Maximum (dB)		50	60	70	79
at RTF (dB)		44	52	62	76
		Basic frequency response			
Frequency range (DIN 45605) (Hz)		100-8200	100-8200	100-7500	100-5500
Reference test gain (dB)		36	43	46	57
Current drain at RTG (mA) 10A/312/13		1.2/1.2/1.2	1.2/1.2/1.2	1.2/1.2/1.2	--/1.2/1.2
Typical battery life (h) 10A/312/13		80/150/260	80/150/260	80/150/260	--/180/260
Equivalent input noise at RTG (dB SPL)		19	19	19	19
Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)		2.0/2.0/1.5	2.0/2.0/1.5	1.0/1.5/1.0	1.5/1.5/1
		Induction coil sensitivity			
at RTF (graph shown for 31.6 mA/m at RTG) (dB SPL)		96	102	106	119
Maximum (1 mA/m at full on gain) (dB SPL)		83	92	102	110
at RTF (1 mA/m at full on gain) (dB SPL)		76	85	94	108
		Electromagnetic compatibility			
EMC immunity by IEC 60118-13, field strength 75/50 V/m, omni IRIL low/high band (dB SPL)		31/41	29/40	34/45	23/32

LEGEND

— Quantum 20 SP
— Quantum 20 HP
— Quantum 20 P
— Quantum 20 M

TEST CONDITIONS

Battery size: 10A/312/13; Source voltage: 1.3 V; Impedance: 7.5 Ohms; Vent: closed at canal end
Tubing 7mm (2cc/OES coupler) – Quantum 20 M, Quantum 20 P, Quantum 20 HP.
Tubing 9 mm (2cc coupler), Tubing 5mm (OES coupler) - Quantum 20 SP.
Measurement data obtained with hearing aid set to linear, omni mode with all adaptive features disabled.
We reserve the right to change specification data without notice as improvements are introduced.