

Quantum™ 6

Micro BTE

Signature features

6 channels

Next generation automatic with SmartFocus

Clients can experience superior automatic performance with the optimal blend of 2 listening environments. In addition, the integration of SmartFocus™ further improves speech understanding in noise or provides optimal comfort automatically

Natural Sound Balance

An adaptive feature to minimize artifacts that can occur when amplified sound combines in the ear canal with direct sound. Natural Sound Balance continuously monitors these sounds and makes precision adjustments to preserve a clear, balanced signal

Automatic Adaptation Manager

Allows for an automatic and smooth adjustment period for the client; providing the best possible first fit acceptance combined with maximum long-term benefit for speech understanding

Next generation feedback manager

Harnessing the power of Unitron's new Era™ platform, the next generation feedback manager offers maximum usable gain by suppressing feedback transients before they become audible

Wireless technology

DuoLink – program, volume and SmartFocus adjustments conducted on one hearing instrument are automatically transferred to the other ear

uDirect (optional) – Wireless interface between hearing instruments and Bluetooth® enabled devices (eg. cell phones)

uTV™ (optional) – streams audio from a TV or audio source to the uDirect


Remote control (optional)

Discreet remote with easy straightforward control of essential features

Additional features

- 3 manual + 3 wireless streaming programs
- IntelliVent technology available on earmolds and sleeve molds
- Multiband adaptive directional microphone
- AntiShock™
- MyMusic™
- Speech enhancement LD
- Noise reduction
- Wind noise manager
- Data logging
- DAI through uDirect
- Optional wireless programming with iCube

Fitting guides



Quantum 6 M
micro BTE

Quantum 6 micro BTE is suitable for fitting mild to severe hearing losses and can fit audiogram configurations ranging from reverse to precipitously sloping.

Quantum 6 micro BTE

Quantum 6 M
micro BTE (slim tube)

Quantum 6 M
micro BTE (earhook)

ANSI 3.22 2003/IEC 118-7 2CC COUPLER TECHNICAL DATA

Reference test frequency - IEC 118-7 (kHz)		1.6	1.6
OSPL90			
Maximum (dB SPL)		126	133
Nominal (dB SPL)		123	130
ANSI HFA (dB SPL)		114	120
at RTF (dB SPL)		111	125
Full on gain (input 50 dB SPL)			
Maximum (dB)		54	57
ANSI HFA (dB)		48	50
at RTF (dB)		45	53
Basic frequency response (ANSI 2003)			
Frequency range (Hz)		< 100-5600	< 100-6000
Reference test gain (dB)		37	43
Current drain at RTG (mA)		1.2	1.25
Typical battery life (h)		140	136
Equivalent input noise at RTG (dB SPL)		19	19
Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)		1/.5/.5	2/1/.5
EMC immunity by ANSI c63.19-2001 EMC, omni		M4	M4

IEC 118-0 OES COUPLER TECHNICAL DATA

Reference test frequency - IEC 118-0 (kHz)		1.6	1.6
OSPL90			
Maximum (dB SPL)		128	133
at RTF (dB SPL)		120	132
Full on gain (input 50 dB SPL)			
Maximum (dB)		60	62
at RTF (dB)		54	61
Basic frequency response			
Frequency range (DIN 45605) (Hz)		< 100-6000	< 100-7100
Reference test gain (dB)		45	54
Current drain at RTG (mA)		1.2	1.2
Typical battery life (h)		140	140
Equivalent input noise at RTG (dB SPL)		19	19
Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)		1/.5/1	2/1/1
EMC immunity by IEC 60118-13, field strength 75/50 V/m, omni		25/26	25/26
IRIL low/high band (dB SPL)			

Legend

- Quantum 6 micro BTE with slim tube
- Quantum 6 micro BTE with earhook

TEST CONDITIONS

Battery size: 312; Source: voltage 1.3 V

The measurements obtained with closed configuration using an HA-1 coupler (ANSI-3.7-1995) or occluded ear simulator (EN 60711, coupling arrangement according to fig.4 in the test standard)

Measurement data obtained with hearing aid set to linear, omni mode with all adaptive features disabled.

Domes should never be fit on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend use of a customized earmold.

We reserve the right to change specification data without notice as improvements are introduced.